

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

Resene

AquaLAQ Clear Coat

furniture, joinery, cabinetry finish

interior waterborne



WARNING

KEEP OUT OF REACH OF CHILDREN

LL1580201F 11/18



SATIN

net contents 1 litre

LL1580201B 11/18

SAFETY PRECAUTIONS

Read label before use. Keep out reach of children. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical attention or advice. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention or advice.

When seeking medical advice take this container with you.

Further information can be obtained from: AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383. NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Use approved waterbased cleaning systems and processes to clean all equipment. Dispose of all waste water and product in an approved manner.

Resene AquaLAQ Clear Coat is a single pack waterborne acrylic, using the latest waterborne technology, designed for kitchens, shop fittings and furniture finishing. Easy to use and fast drying to an extremely durable finish. The rheology of Resene AquaLAQ minimises applicator error. Available in three sheen levels - gloss, satin and matte.

Preparation

- Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.
- All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.
- For new work ensure the surface is sanded to a smooth finish and dusted off. Round all sharp edges. Ensure the surface is dry before painting.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Priming

- Sand all wood substrates, then prime/seal with Resene AquaLAQ Quick Dry Sealer or Resene AquaLAQ NGR Primer Sealer.
- Repaints - spot prime all bare areas with the same primer shown for new work and proceed as for new work.

Application

- Ensure you have read the detailed Resene AquaLAQ application sheet available from Resene prior to application of product.
- Apply 1-2 coats by spray allowing at least 30 minutes in ideal conditions, before recoating.
- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system. Multiple air changes are required during application and until product is cured sufficiently. Ensure humidity is less than 65% and temperature 15-25°C for ideal application and curing. Poor ventilation may affect appearance and performance.

Maintenance

(after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colour. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Quick check

Use on: Kitchens, shop fittings and furniture finishing, over correctly prepared MDF board and wood substrates. **Gloss level:** Gloss, satin and matte.

Coverage: 8-10 square metres per litre per coat.

Dry time (minimum): Touch dry 10-15 minutes.

Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system. Multiple air changes are required during application and until product is cured sufficiently. Ensure humidity is less than 65% and temperature 15-25°C for ideal application and curing. Poor ventilation may affect appearance and performance.

Recoat time (minimum): 30 minutes.

Serviceable after: While the coating is serviceable after 48 hours depending on film thickness, tint level and drying conditions, it will still be in the curing stage so care needs to be taken with contact and wiping.

Primer required: Yes.

Usual number of coats: 1-2.

Application method: Spray - pressure pot, suction or gravity.

Thinning: Do not thin. Consult Resene if needed.

Clean up: Water.

Colour range: Clear.

Before use: Stir well with a wide flat stirrer, mixing from the bottom of the pail towards the top.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Resene

Resene

the paint the professionals use

Automotive & Light Industrial

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Resene Automotive & Light Industrial
PO Box 62282, Mt Wellington Mail Centre, Auckland 1060
Call (09) 259 2738, Fax (09) 259 2937
visit www.rall.co.nz or email us at info@rall.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAJ, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.

