

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

DANGER

KEEP OUT OF REACH OF CHILDREN



www.designpine.com

net contents 1 litre

A-LL37501 12/16

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May be harmful if swallowed. Harmful if inhaled. Causes eye irritation. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Use only outdoors or in a well ventilated area. Use personal protective equipment as required. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release to the environment. Contaminated work clothing should not be allowed out of the workplace. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Immediately call a POISON CENTRE, doctor, physician or first aider.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned: Get medical advice or attention.

If medical attention is required: Have product container or label at hand. Further information can be obtained from:

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or from the Resene Help Line 0800 737 363.

AUST: POISONS INFORMATION CENTRE 131 126 or from the Resene Help Line 1800 738 383.

CONTAINS: Isoparaffins Petroleum Hydrotreated HFP 250-520 gms/L, Naphtha Petroleum, Light Aromatic Solvent 120-250 gms/L, Barium Metaborate <15 gms/L, Naphtha Petroleum, heavy Hydrodesulfurised <15 gms/L, Methyl Ethyl Ketoxime <15 gms/L. For use as a decorative/protective coating.

SPILLS Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

FIRE Use foam, carbon dioxide or dry chemical powder.

exterior primer



**DESIGNPINE
BLUE**

Design Pine Primer has been formulated for use on a wide variety of both treated (including LOSP) and untreated timber surfaces as well as spot priming for Design Pine pre-primed timber.

Preparation

- If the surface you propose is unsound or not referred to, try a small test area first or contact your local paint merchant for advice.
- Ensure surfaces to be painted are in sound condition, thoroughly sanded, dry, free from dirt, dust and loose material, oil and grease.
- Round all sharp timber edges. Any bare timber surface that has been left exposed to the weather for more than one week must be thoroughly sanded.
- **All sanding dusts can be harmful and appropriate protection should be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos can be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- Ensure new treated timber (including LOSP) has been well ventilated prior to applying the primer to allow excess treatment solvents to evaporate.
- Fill cracks and holes with an appropriate filler after priming.

Application

- Apply one full coat. Allow 24 hours to dry. Design Pine Primer is best applied by brush to ensure full surface wetting is achieved.
- Where possible prime all timber faces with particular attention to end grains, nail heads, splits, corners and joints.
- Pre-primed surfaces exposed to the weather for extended periods of time may become chalky. If this occurs, sand and re-prime the surface.

Overcoating

- Design Pine Primer requires a minimum of two full topcoats to be applied.
- Timber is a natural substrate so select light colour topcoats for maximum life. Dark colours absorb light and heat, which can lead to a number of problems including distortion, surface cracking or gum bleeding. Your local paint merchant can advise you on the reflectance value of the colour you have selected - the higher the reflectance value the less heat the substrate absorbs and the longer the expected life of the paint finish.
- Design Pine Primer should not be exposed to the weather for long periods. Consult your local paint merchant if recoating after 4-6 weeks. Design Pine Primer is best overcoated within 6 weeks of installation for optimum finish results.
- Under certain conditions waterborne paints may crawl or ciss over Design Pine Primer. Wiping with clean turps or a dilute detergent solution will rectify the condition.

Caring for your paint finish

Annual washing of your home will help maintain its fresh appearance. For an instant fresh appearance regularly wash down with a mild detergent diluted as recommended with water. Apply the diluted solution with a soft broom. Wash off with copious amounts of freshwater. Most detergents can have a negative effect on fish life so avoid letting the washings run off into the stormwater system. Allow the full paint system 4 full weeks' cure prior to undertaking any cleaning of the surface.



UN No. 1263 - Paint related product

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, sparks, open flames and hot surfaces. No smoking.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 785, Beenleigh, Qld, 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAJ, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Exterior and interior woodwork.

Gloss level: Low sheen.

Coverage: 16 square metres per litre per coat.

Dry time: 4-6 hours at 20°C.

Low temperatures, high humidity and/or high residual treatment solvents will slow drying. Do not apply under damp conditions.

Recoat time: 24 hours.

Number of coats: One.

Application method: Brush.

Thinning and clean up: Mineral turps.

Colour range: Pale blue.

Before use: Stir well with a wide flat stirrer.

Design Pine Primer meets the Requirements of AS 3730.13 - 1991 Standard.

In every case it is recommended that the appropriate Safety Data Sheet is consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.