

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre

LL2282001 3/15

WARNING

Read label before use. Keep out reach of children. Harmful if swallowed. Causes mild skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Wear protective gloves and clothing, eye and face protection. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, intrinsically safe equipment. Use only non-sparking tools. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.
IF ON SKIN (or hair): Take off contaminated clothing and wash before re-use. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention or advice.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
If exposed or concerned get medical attention.
When seeking medical advice take this container with you.
Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.
NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.
CONTAINS: Naphtha, Petroleum Hydrodesulfurised Heavy 250-450 gms/L, Naphtha Petroleum, Light Aromatic Solvent 80-180 gms/L, 1,2,4-Trimethyl Benzene 15-50 gms/L, Solvent Naphtha Petroleum Heavy Aromatic < 5 gms/L, (2-Benzothiazoylthio) Butanedioic Acid < 5 gms/L.
For use as a decorative/protective coating.
For full technical instructions see Data Sheet D503.
SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.
Cleaning Paint Equipment: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.
FIRE: Use foam, carbon dioxide or dry chemical powder.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Furniture and Decking Oil

exterior



Resene Furniture and Decking Oil is designed for direct application to timber decks and furniture to enhance and restore the timber colour and provide protection against water, fungi, and U.V. light. The product is designed for annual application to keep decks and furniture in good condition and assist with water repellency.

Preparation

- Treatment with Resene Timber and Deck Wash (see Data Sheet D813) is recommended for all substrates to remove dirt, natural stains and enhance the degree of product penetration. Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- Always trial Resene Furniture and Decking Oil on a representative piece of timber first to ensure it gives the result you want on the actual timber you are coating.
- This product may be used to treat a wide variety of timber surfaces. If the surface you propose to treat is not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

- Resene Furniture and Decking Oil is recommended as an annual pre-season maintenance treatment of pine decks, furniture and Cedar garage doors. New timber should be treated with Resene Furniture and Decking Oil before assembly. Pay special attention to the underside of decks, as they will be difficult to coat after the deck has been assembled. All faces of the timber should be treated with special attention to end grains.
- Before use and regularly during use, stir well with a wide flat stirrer.
- Saturate the surface with Resene Furniture and Decking Oil. The worst weathered surfaces will require a second application.
- Resene Furniture and Decking Oil will not penetrate existing coatings or very hard latewood bands. Wipe excess Resene Furniture and Decking Oil off with a dry, absorbent, lint free cloth rubbing along the grain.
- If applying two coats, apply the second coat after 24 hours and preferably before one week. Protection begins after the full system has been applied.
- Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.

- Will typically need to be applied every spring and more frequently if a continuous water-beading effect is desired. Performance is related to the depth of colour applied. Light applications and dressed surfaces may require maintenance sooner, while heavier applications and rough sawn surfaces will require less maintenance.

Precautions

- Contains powerful fungicides. Avoid skin contact and wear gloves when wiping off any excess.
- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d).

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 – PAINT



Resene

the paint the professionals use



In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAJ, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Exterior timber decks, furniture and Cedar garage doors.

Gloss level: None. Fully penetrating.

Coverage: New dressed timber is effectively treated at 10-12 square metres per litre per coat; badly weathered surfaces may take up to 3 square metres per litre per coat and may require a second application.

Dry time (minimum): 24 hours. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 24 hours.

Usual number of coats: 1-2.

Application method: Brush, spray or roller.

Thinning and clean up: Do not thin. Clean up with mineral turps.

Colour range: Natural

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.