

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre

A-LL3850001 4/19

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May be harmful if swallowed. Causes mild skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Remove all contaminated clothing and wash before reuse. Wash skin with plenty of soap and water. If skin irritation or rash occurs get medical attention or advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

Call a POISON CENTRE, doctor or physician if you feel unwell. When seeking medical advice take this container with you. Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a surface preparation coating. For full technical instructions see Data Sheet D42.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: Use foam, carbon dioxide or dry chemical powder.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Sureseal pigmented sealer exterior/interior



Resene Sureseal is a pigmented, solventborne, alkali-resistant, penetrating sealer with the ability to penetrate and bond to porous, powdery and alkaline surfaces making them suitable for painting. This lower odour formulation acts as a surface conditioner that also reduces bleeding of water stains and dries without the unwanted and strong solvent odours associated with traditional solventborne products.

Preparation

• Ensure surfaces are thoroughly sanded, dry, free from dirt, dust and loose material. A wipe with a damp cloth or sponge will remove most sanding dust.

• Waterblasting is the best surface preparation prior to painting of weathered cementitious surfaces.

• Oil and grease must be removed using Resene Paint Prep and Housewash (see Data Sheet D812).

• If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• Efflorescence on masonry must be treated (see Data Sheet D83).

• Fill cracks and holes with an appropriate filler before sealing.

• Where staining is present the source must be removed.

• Plasterboard must be prepared to an appropriate level of finish. Resene Broadwall Surface Prep & Seal (see Data Sheet D807) or Resene Broadwall 3 in 1 (see Data Sheet D810) is recommended to achieve a level 5 finish.

• All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

• Resene Sureseal should not be exposed to the weather for long periods or applied to wet or damp surfaces.

• Consult your Resene ColorShop or Reseller for technical advice on painting of old cementitious roof tiles.

• This product may be used to seal a wide variety of surfaces. If the surface you propose to seal is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

• Generally one coat is sufficient. Where superior barrier protection/stain resistance is required two coats are recommended.

• When sealing badly weathered cementitious surfaces Resene Sureseal is best applied by brush to ensure full surface wetting it is achieved.

• Sanding of plasterboard can loosen fibres that Resene Sureseal will then lock in place. Lightly resand after Resene Sureseal has dried.

• Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting in marginal

painting conditions. Do not use gas or diesel burners to heat coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.

• Resene Sureseal is a penetrating sealer and should not be regarded as forming part of the subsequent coating build up. One coat of Resene Sureseal cannot be expected to hold back gross staining. The source of the stain must be removed and more than one coat of Resene Sureseal employed.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment.

Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.



UN NO. 1263 – PAINT RELATED PRODUCT

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, sparks, open flames and hot surfaces. No smoking.



Sureseal SDS

Resene

the paint the professionals use



Sureseal TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wqtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Metal packaging includes recycled material and is printed using U.V. inks and varnishes ensuring energy savings and no emissions.

Quick check

Use on: Exterior and interior surfaces including paperfaced plasterboard, hardboard, softboard, gypsum plaster (solid and fibrous) and all aged and powdery cementitious surfaces. Recommended for priming cement based paints and limewashes prior to overpainting and as a surface conditioner to reduce the bleeding of water and rust stains.

Gloss level: Low sheen.

Coverage: 16 square metres per litre per coat, dependent on surface porosity.

Dry time (minimum): 45 minutes at 20°C. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 3 hours at 20°C.

Usual number of coats: Usually one.

Application method: Brush, synthetic roller and spray. Best applied by brush to ensure full surface wetting.

Thinning: Resene Thinner No.2 (lower odour) or Mineral turps.

Clean up: Resene Thinner No.2 (lower odour), Mineral turps or Resene Brush Cleaner.

Colour: Off-white.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.