

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre

tinter included

LL22901 4/18

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May cause an allergic skin reaction. Suspected of damaging fertility or unborn child. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

AVOID BREATHING MISTS, VAPOURS, SPRAYS. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Use personal protective equipment as required. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention or advice. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention or advice.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Seek medical attention or advice if you feel unwell.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1 800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: 3-Iodo-2-Propynyl Butyl Carbamate 1-5 gms/L, Diuron 1-5 gms/L, Benzotriazol derivatives 1-5 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D57a.

If using this product tinted to a Resene CoolColour™, see Data Sheet D57C.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

water borne **Woodsman**

penetrating oil stain

exterior



Resene Waterborne Woodsman is a waterborne woodstain matching the needs of timber to the desire to achieve the most natural appearance possible.

Preparation

- Treatment with Resene Timber and Deck Wash (see Data Sheet D813) is recommended for all substrates to remove dirt, natural stains and enhance the degree of product penetration.
- Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.
- Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- Always colour test first to check your choice of Resene Waterborne Woodsman colour gives the result you want on the actual timber you are staining.
- Consult your Resene ColorShop or Reseller for advice on coating severely weathered surfaces, exotic timbers, non-standard timbers and exterior doors and windows.
- Stains are not acceptable finishes for substrates that will be used in the collection of rainwater for drinking purposes. Only products that are expressly recommended for use in rainwater collection should be considered.
- This product may be used to stain a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Precautions

- Contains powerful fungicides.
- Avoid skin contact.
- Will not prevent checking of plywood.
- Where alkaline cleaners (including Resene Moss & Mould Killer) are used in the preparation of the substrate, ensure that any residue is removed by hosing down with clean water. These residues can affect film formation and, subsequently, durability.

Application

- Any movement of weatherboards (board dimensional

changes) will be exacerbated with darker colours. A CoolColour version will reflect more heat compared to the standard colour. However, this will reduce the potential for dimensional changes rather than necessarily eliminate it. If weatherboards move uncoated board or previous coats of stain may become visible. This is not a stain fault, but due to excessive movement in the weatherboards. If in doubt, use a lighter colour option to minimise heat build-up.

- Before use and regularly during use, stir well with a wide flat stirrer.
- Apply one full coat and allow to dry before applying second coat if required.
- All faces of the timber should be treated with special attention to end grains.
- For new work apply the second coat preferably before one week. Protection begins after full system is applied.
- Will typically require maintenance after two to three summers. Performance is related to the depth of colour applied. Light applications, light colours and dressed surfaces may require maintenance sooner, while heavier applications, darker colours and rough sawn surfaces will require less maintenance.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.



Waterborne Woodsman SDS



Waterborne Woodsman TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAJ, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Timber surfaces.

Gloss level: None. Fully penetrating over bare timber.

Typical coverage: (a) Dressed timber:

1st coat, 10-12 square metres per litre,

2nd coat, 12-14 square metres per litre.

(b) Rough sawn timber:

1st coat, 4-6 square metres per litre,

2nd coat, 9-11 square metres per litre.

(c) Badly weathered timber:

1st coat, 3-4 square metres per litre,

2nd coat 5-7 square metres per litre.

Dry time (minimum): 45 minutes. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours.

Primer required: No.

Usual number of coats: Two. Will require maintenance after two to three summers.

Application method: Brush, roller or spray.

Thinning and clean up: Do not thin. Clean up with water when wet or mineral turps when dry.

Colour range: Standard colours, refer Resene Exterior timber stains colour chart.

Also available as Resene Waterborne Woodsman CoolColour to help reflect heat from exterior surfaces. Application of a Resene CoolColour will reflect more heat than the same colour made using non-cool pigmentation and reduce heat related stress on the substrate; it will not make the stained surface cool to touch. Check with Resene staff whether a Resene CoolColour is right for your project.

Before use: Stir well with a wide flat stirrer and also stir during application.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.