

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

# Resene

## Woodsman Cedar Natural Wood Oil

exterior/interior

**WARNING**  
KEEP OUT OF REACH OF CHILDREN



**CLEAR**  
(must be tinted  
for exterior use)

LL2250001F 2/24

# net contents 1 litre

LL2250001B 2/24

## SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May cause an allergic skin reaction. Suspected of damaging fertility or unborn child. Harmful to aquatic life with long lasting effects.

## PRECAUTIONS

AVOID BREATHING MISTS, VAPOURS, SPRAYS, DO NOT EAT, DRINK OR SMOKE WHILE USING. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Obtain special instructions before use. Wear protective gloves and clothing. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

## FIRST AID

IF SWALLOWED: Rinse mouth.

IF ON SKIN (or hair): Wash with plenty of water. If skin irritation occurs get medical advice. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention or advice.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Seek medical attention or advice if you feel unwell.

When seeking medical advice take this container with you.

Further information can be obtained from AUST. POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363. CONTAINS: Zirconium Octoate 1-5 g/L

For use as a decorative/protective coating.

For full technical instructions, see Data Sheet D514, or when using as a CoolColour, see Data Sheet D514C.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

## CLEANING PAINT EQUIPMENT:

Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Woodsman Cedar Natural Wood Oil is a non-film forming penetrating wood oil stain designed to enhance and protect exterior and interior timber walls and ceilings.

## Preparation

- Ensure substrates to be coated are in sound condition, dry, free from dirt, dust and loose material.
- If mould or algae is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Scrub new timber with Resene Timber and Deck Wash (see Data Sheet D813) to remove dirt, natural stains and enhance the degree of stain penetration. DO NOT water blast timber, as this has the potential to damage the timber surface and compromise durability of the finish. New Vitex decking may undergo a colour change with sections turning green, if this occurs apply a solution of white vinegar thinned with an equal part of water, scrub down then thoroughly rinse.
- For reprints of existing penetrating stains remove any gross contamination and loose cellulose fibres by sanding and prepare as per new.
- **Some timber sanding dusts may be harmful and appropriate protection to prevent inhalation must be worn.**

• The final colour will not be seen until the full number of coats has been applied. Always colour test first to check your choice of Resene Woodsman Cedar Natural Wood Oil colour gives the result you want on the actual timber you are staining.

- Consult your Resene ColorShop or reseller for advice on coating severely weathered surfaces, exotic timbers, non-standard timbers and exterior doors and windows.
- Stains are not acceptable finishes for substrates that will be used in the collection of rainwater for drinking purposes. Only products that are expressly recommended for use in rainwater collection should be considered.

## Precautions

- Contains fungicides. Avoid skin contact.
- Will not prevent checking of plywood.
- Where alkaline cleaners (including Resene Moss & Mould Killer) are used in the preparation of the substrate, wash the treated surface well with clean water. These residues can affect film formation and, subsequently, durability.

## Application

- Resene Woodsman Cedar Natural Wood Oil Stain cannot be applied over an existing film forming or mineral oil stain type.
- Timber dimensional changes will be exacerbated with dark stain colours.
- A Resene CoolColour version will reflect more heat compared to the standard colour. This will reduce but not eliminate the potential for timber dimensional changes. If weatherboards do undergo surface heat induced dimensional changes a line at the intersection of boards or previous coats of stain may become visible. Use a lighter colour option to minimise heat build-up.
- Stir well with a wide flat stirrer before use and regularly during use.
- Do not apply over mineral oils or film forming stains.
- Apply one full coat and allow to dry before applying the second coat. For new work apply the second coat preferably before one week. Protection begins after full system has been applied.
- For the optimum finish, envelope apply the first coat of stain, including sealing of cut or mitred ends.
- Will not penetrate through existing coatings or very hard latewood bands. For best results, wipe excess Resene Woodsman Cedar Natural Wood Oil off with a dry, absorbent, lint-free cloth rubbing along the grain.

## Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

## Quick check

**Use on:** Timber surfaces, including dressed and band sawn, Cedar/Redwood, weatherboards, engineered timbers, plywood and profiled sheets. **DO NOT APPLY ON DECKS OR FURNITURE.**

**Gloss level:** None when fully penetrated.

**Typical coverage (coverage will vary with timber species and condition):** Dressed timber: First coat 10-12 square metres per litre. Second coat 12-14 square metres per litre. Depending on the timber's porosity and the selected a third coat may be required in 3-6 months. Band sawn and weathered timber: First coat 3-4 square metres per litre. Second coat 5-7 square metres per litre.

**Touch dry:** 4 hours @ 18°C.

**Recoat time (minimum):** 24 hours. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions. Rain resistance is normally achieved in 8 hours @ 18°C.

**Primer required:** No.

**Usual number of coats:** Two. Depending upon exposure, maintenance will be required after 2-3 summers.

**Application method:** Use a synthetic brush for cutting in. Apply using a Resene Deckmaster brush or lambswool Swiss Mop applicator.

**Thinning and clean up:** Do not thin. Clean up with water when wet or mineral turps when dry.

**Colour range:** Standard colours, refer Resene Natural Wood Oil colour chart. This product may also be tinted to colours from the Resene Exterior timber stains colour chart. The clear untinted finish can only be used as an interior clear for timber walls/ceilings. The clear product contains no UV protection for exterior timbers. Product may look more opaque or milky until dry. Avoid applying excessive product as this may affect curing.

Also available as Resene Woodsman Cedar Natural Wood Oil CoolColour. Check with Resene staff whether a Resene CoolColour is right for your project.

**Before use:** Stir well with a wide flat stirrer before use and regularly during use.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.  
Read the appropriate Data Sheet and Safety Data Sheet before application.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

# Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 918, Ashmore City, QLD 4214  
Ph 1800 738 383 Visit [resene.com.au](http://resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [resene.co.nz](http://resene.co.nz)

